

**Amendments to the Claims:**

The following listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) An image scanning apparatus comprising:  
an illuminating device, ~~which~~ that irradiates illumination;  
an image sensor, ~~which~~ that outputs signal charges as image data of an original, including a light receiving part for receiving light, in which the light is an illumination irradiated from said illuminating device and influenced by the original, and includes a transferring unit for transferring signal charges generated at the light receiving part; and

a controlling device, ~~which~~ that instructs said illuminating device to irradiate illumination, and directs a timing to transfer signal charges to said transferring unit under a predetermined condition, wherein:

said illuminating device respectively irradiates upon the original as the illumination, light to be shut out other than at the light receiving part of said image sensor and light having a long wavelength not to be shut out other than at the light receiving part of the image sensor; and

said controlling device prohibits the light having a long wavelength from being irradiated by said illuminating device during the period in which the image data of the original is being output through the transferring unit of said image sensor.

2. (Cancelled)

3. (Currently Amended) The image scanning apparatus according to ~~claim~~ claim 1, wherein:

said image sensor discharges signal charges not corresponding to the image data of the original as invalid data; and

said controlling device permits the light having a long wavelength to be irradiated by said illuminating device during the period in which the invalid data is being discharged by said image sensor.

4. (Currently Amended) The image scanning apparatus according to ~~claim~~ claim 1, wherein:

the light having a long wavelength irradiated upon the original by said illuminating device is light ~~which~~that is received with low photosensitivity by a normal image on the original, and is shut out by a defect on the original; and

said controlling device detects a defect on the original based on image data of the original output from said image sensor, the image data obtained by said light having a long wavelength.

5. (Currently Amended) The image scanning apparatus according to claim 1, wherein:

~~—————said illuminating device respectively irradiates light upon the original as the illumination, to be shut out other than at the light receiving part of said image sensor and light having a long wavelength not to be shut out other than at the light receiving part of said image sensor; and~~

said controlling device permits the light having a long wavelength to be irradiated by said illuminating device, prior to irradiation of the light to be shut out other than at the light receiving part of said image sensor, the light having a long wavelength irradiated during the period in which data not corresponding to image data of the original is being output through the transferring unit of said image sensor.

6. (Cancelled)

7. (Currently Amended) The image scanning apparatus according to claim 5, wherein:

the light having a long wavelength irradiated upon the original by said illuminating device is light ~~which~~that is received with low photosensitivity by a normal image on the original, and is shut out by a defect on the original; and

said controlling device detects a defect on the original based on image data of the original output from said image sensor, the image data obtained by said light having a long wavelength.

8. (Currently Amended) An image scanning apparatus comprising:  
an illuminating device for irradiating illumination on an original;  
an imaging device for reading out signal charges from a light receiving part and outputting said signal charges as image data of the original, including said light receiving part for receiving light and for generating said signal charges, in which the light is an illumination irradiated from said illuminating device and influenced by the original; and  
a controlling device for directing said illuminating device to irradiate illumination, directing said imaging device to read out the signal charges generated by said light receiving part, and prohibiting ~~illumination from irradiating in~~ said illuminating device ~~while~~from irradiating any illumination onto the original during the time at which image data of the original is being output from said imaging device.

9. (Previously Presented) The image scanning apparatus according to claim 8, wherein:

said imaging device  
has a line sensor comprising a plurality of the light receiving parts arranged in one dimension, a charge-to-voltage converter which converts the signal charges to voltages and outputs the voltages, a charge readout part which reads out the signal charges generated by said light receiving parts, and a charge transfer part which transfers the signal charges read out by said charge readout part to said charge-to-voltage converter, and

outputs image data of the original for every line while moving at least one of said line sensor and the original in a direction orthogonal to the direction said light receiving parts are arranged in; and

said controlling device directs said charge readout part to periodically read out one line of the signal charges generated by said light receiving parts and prohibits illumination from irradiating in said illuminating device while said signal charges are converted to the voltages by said charge-to-voltage converter and then output as image data of the original.

10. (Original) The image scanning apparatus according to claim 9, wherein:

said imaging device at least outputs signal charges generated by said charge-to-voltage converter as invalid data that does not correspond to image data of the original, while illumination is irradiating from said illuminating device.

11. (Currently Amended) A recording medium which stores an image scanning program which causes a computer to execute the step of:

controlling an image scanning apparatus having

an illuminating device for irradiating illumination on an original and

an imaging device for reading out signal charges from a light receiving part and outputting said signal charges as image data of the original, including said light receiving part for receiving light and for generating said signal charges, in which the light is an illumination irradiated from said illuminating device and influenced by the original; wherein said controlling step includes

a controlling procedure for directing said illuminating device to irradiate illumination, directing said imaging device to read out the signal charges generated by said light receiving part, and prohibiting ~~illumination from irradiating in~~ said illuminating device ~~while from~~

irradiating any illumination onto the original during the time at which image data of the original is being output from said imaging device.

12. (Previously Presented) The recording medium which stores an image scanning program according to claim 11, wherein:

said imaging device

has a line sensor comprising a plurality of the light receiving parts arranged in one dimension, a charge-to-voltage converter which converts the signal charges to voltages and outputs the voltages, a charge readout part which reads out the signal charges generated by said light receiving parts, and a charge transfer part which transfers the signal charges read out by said charge readout part to said charge-to-voltage converter, and

outputs image data of the original for every line while moving at least one of said line sensor and the original in a direction orthogonal to the direction said light receiving parts are arranged in; and

said controlling procedure directs said charge readout part to periodically read out one line of the signal charges generated by said light receiving parts and prohibits illumination from irradiating in said illuminating device while said signal charges are converted to the voltages by said charge-to-voltage converter and then output as image data of the original.

13. (Currently Amended) A data structure for coding and transmitting an image scanning program which causes a computer to execute the step of:

controlling an image scanning apparatus comprising:

an illuminating device for irradiating illumination on an original; and

an imaging device for reading out signal charges from a light receiving part and outputting said signal charges as image data of the original, including said light receiving part for receiving light and for generating said signal charges, in which the light is

an illumination irradiated from said illuminating device and influenced by the original;  
wherein the controlling step includes

directing said illuminating device to irradiate illumination, directing said imaging device to read out the signal charges generated by said light receiving part, and prohibiting ~~illumination from irradiating in~~ said illuminating device ~~while~~ from irradiating any illumination onto the original during the time at which image data of the original is being output from said imaging device.

14. (Previously Presented) The data structure according to claim 13, wherein:

said imaging device

has a line sensor comprising a plurality of the light receiving parts arranged in one dimension, a charge-to-voltage converter which converts the signal charges to voltages and outputs the voltages, a charge readout part which reads out the signal charges generated by said light receiving parts, and a charge transfer part which transfers the signal charges read out by said charge readout part to said charge-to-voltage converter, and

outputs image data of the original for every line while moving at least one of said line sensor and the original in a direction orthogonal to the direction said light receiving parts are arranged in; and

said controlling step directs said charge readout part to periodically read out one line of the signal charges generated by said light receiving parts and prohibits illumination from irradiating in said illuminating device while said signal charges are converted to the voltages by said charge-to-voltage converter and then output as image data of the original.